

# RT-FL-YFL5028A-02

线扫相机, 50mm焦距 F/2.8, F接口, 工作距离242-361mm


## 参数

### 光学说明书

Focal length	(mm)	50
Magnification		0.23 - 0.15
Image circle Ø	(mm)	45
Max detector size		35 mm format
Working distance	(mm)	242 - 361
F/#		2.8 - 22
Back focal length	(mm)	30.43 - 34.54

### 机械性能

接口		F
长度	(mm)	63.6
直径	(mm)	60
Filter thread		M52x0.75
重量	(g)	425
Focus lock		Yes
Iris lock		Yes



## 兼容产品



### LTDM 系列 漫射频闪圆顶照明灯

LTDMA1-R	Diffusive strobed dome illuminator - small size medium power red
LTDMA1-G	Diffusive strobed dome illuminator - small size medium power green
LTDMA1-W	Diffusive strobed dome illuminator - small size medium power white
LTDMB2-R	Diffusive strobed dome illuminator - medium size high power red
LTDMB2-G	Diffusive strobed dome illuminator - medium size high power green
LTDMB2-W	Diffusive strobed dome illuminator - medium size high power white
LTDMC1-W	Diffusive strobed dome illuminator - large size medium power white
LTDMC2-R	Diffusive strobed dome illuminator - large size high power red
LTDMC2-G	Diffusive strobed dome illuminator - large size high power green
LTDMC2-W	Diffusive strobed dome illuminator - large size high power white



### LTDMLA 系列 漫射频闪圆顶+小角度照明系统

LTDMLAB2-WW	Diffusive strobed dome + low angle illumination system - medium size high power white
LTDMLAC1-WW	Diffusive strobed dome + low angle illumination system - large size medium power white
LTDMLAC2-WW	Diffusive strobed dome + low angle illumination system - large size high power white