

RT-FL-YFL5028A-035

线扫相机，50mm焦距 F/2.8，F接口， 佛能否做距离146-201mm

参数

光学说明书		
Focal length	(mm)	50
Magnification		0.4 - 0.28
Image circle Ø	(mm)	45
Max detector size		35 mm format
Working distance	(mm)	146 - 201
F/#		2.8 - 22
Back focal length	(mm)	37.16 - 43.29

机械性能		
接口		F
长度	(mm)	70.4
直径	(mm)	60
Filter thread		M52x0.75
重量	(g)	435
Focus lock		Yes
Iris lock		Yes

兼容产品



LTDMA 系列
漫射频闪圆顶照明灯

LTDMA1-R	Diffusive strobed dome illuminator - small size medium power red
LTDMA1-G	Diffusive strobed dome illuminator - small size medium power green
LTDMA1-W	Diffusive strobed dome illuminator - small size medium power white
LTDMB2-R	Diffusive strobed dome illuminator - medium size high power red
LTDMB2-G	Diffusive strobed dome illuminator - medium size high power green
LTDMB2-W	Diffusive strobed dome illuminator - medium size high power white
LTDMC1-W	Diffusive strobed dome illuminator - large size medium power white
LTDMC2-R	Diffusive strobed dome illuminator - large size high power red
LTDMC2-G	Diffusive strobed dome illuminator - large size high power green
LTDMC2-W	Diffusive strobed dome illuminator - large size high power white



LTDMLA 系列
漫射频闪圆顶+小角度照明系统

LTDMLAB2-WW	Diffusive strobed dome + low angle illumination system - medium size high power white
LTDMLAC1-WW	Diffusive strobed dome + low angle illumination system - large size medium power white
LTDMLAC2-WW	Diffusive strobed dome + low angle illumination system - large size high power white

