



RT-VHF16MK

适用于1"探测器的五百万像素镜头, 焦距16 mm, F值1.4, C接口

参数

光学规格

Focal length	(mm)	16
像圈直径	(mm)	16
Max detector size		1"
工作距离	(mm)	300 - ∞
F/#		1.4
Back focal length	(mm)	12.6
Distortion	(%)	-1.00
Nominal resolving power	(μm)	46

机械性能

接口	C	
长度	(mm)	53
直径	(mm)	42
Filter thread		M35.5x0.5
质量	(g)	140
Focus lock screws		Yes
Iris lock screws		Yes

兼容产品



LTDM series

High-power strobed LED domes

LTDMA1-R	Diffusive strobed dome illuminator - small size medium power red
LTDMA1-G	Diffusive strobed dome illuminator - small size medium power green
LTDMA1-W	Diffusive strobed dome illuminator - small size medium power white
LTDMB2-R	Diffusive strobed dome illuminator - medium size high power red
LTDMB2-G	Diffusive strobed dome illuminator - medium size high power green
LTDMB2-W	Diffusive strobed dome illuminator - medium size high power white
LTDMC1-W	Diffusive strobed dome illuminator - large size medium power white
LTDMC2-R	Diffusive strobed dome illuminator - large size high power red
LTDMC2-G	Diffusive strobed dome illuminator - large size high power green
LTDMC2-W	Diffusive strobed dome illuminator - large size high power white



LTDMA series

High-power strobed LED dome + low angle lights

LTMLAB2-WW	Diffusive strobed dome + low angle illumination system - medium size high power white
LTMLAC1-WW	Diffusive strobed dome + low angle illumination system - large size medium power white
LTMLAC2-WW	Diffusive strobed dome + low angle illumination system - large size high power white

