



# RT-VHF25MK

适用于1"探测器的五百万像素镜头, 焦距25 mm, F值1.4, C接口

## 参数

### 光学规格

Focal length	(mm)	25
像圈直径	(mm)	16
Max detector size		1"
工作距离	(mm)	300 - ∞
F/#		1.4
Back focal length	(mm)	16.5
Distortion	(%)	-1.00
Nominal resolving power	(μm)	50

### 机械性能

接口		C
长度	(mm)	43
直径	(mm)	42
Filter thread		M35.5x0.5
质量	(g)	140
Focus lock screws		Yes
Iris lock screws		Yes

## 兼容产品



### LTDM series

High-power strobed LED domes

<b>LTDMA1-R</b>	Diffusive strobed dome illuminator - small size medium power red
<b>LTDMA1-G</b>	Diffusive strobed dome illuminator - small size medium power green
<b>LTDMA1-W</b>	Diffusive strobed dome illuminator - small size medium power white
<b>LTDMB2-R</b>	Diffusive strobed dome illuminator - medium size high power red
<b>LTDMB2-G</b>	Diffusive strobed dome illuminator - medium size high power green
<b>LTDMB2-W</b>	Diffusive strobed dome illuminator - medium size high power white
<b>LTDMC1-W</b>	Diffusive strobed dome illuminator - large size medium power white
<b>LTDMC2-R</b>	Diffusive strobed dome illuminator - large size high power red
<b>LTDMC2-G</b>	Diffusive strobed dome illuminator - large size high power green
<b>LTDMC2-W</b>	Diffusive strobed dome illuminator - large size high power white



### LTDMLA series

High-power strobed LED dome + low angle lights

<b>LTDMLAB2-WW</b>	Diffusive strobed dome + low angle illumination system - medium size high power white
<b>LTDMLAC1-WW</b>	Diffusive strobed dome + low angle illumination system - large size medium power white
<b>LTDMLAC2-WW</b>	Diffusive strobed dome + low angle illumination system - large size high power white

