



RT-VHF50MK

适用于1"探测器的五百万像素镜头, 焦距50 mm, F值1.4, C接口

参数

光学规格

| | | |
|-------------------------|------|---------|
| Focal length | (mm) | 50 |
| 像圈直径 | (mm) | 16 |
| Max detector size | | 1" |
| 工作距离 | (mm) | 500 - ∞ |
| F/# | | 1.4 |
| Back focal length | (mm) | 14.8 |
| Distortion | (%) | 0.05 |
| Nominal resolving power | (μm) | 44 |

机械性能

| | | |
|-------------------|------|-----------|
| 接口 | | C |
| 长度 | (mm) | 48 |
| 直径 | (mm) | 48 |
| Filter thread | | M40.5x0.5 |
| 质量 | (g) | 200 |
| Focus lock screws | | Yes |
| Iris lock screws | | Yes |

兼容产品



LTDMA series
High-power strobed LED domes

| | |
|-----------------|--|
| LTDMA1-R | Diffusive strobed dome illuminator - small size medium power red |
| LTDMA1-G | Diffusive strobed dome illuminator - small size medium power green |
| LTDMA1-W | Diffusive strobed dome illuminator - small size medium power white |
| LTDMB2-R | Diffusive strobed dome illuminator - medium size high power red |
| LTDMB2-G | Diffusive strobed dome illuminator - medium size high power green |
| LTDMB2-W | Diffusive strobed dome illuminator - medium size high power white |
| LTDMC1-W | Diffusive strobed dome illuminator - large size medium power white |
| LTDMC2-R | Diffusive strobed dome illuminator - large size high power red |
| LTDMC2-G | Diffusive strobed dome illuminator - large size high power green |
| LTDMC2-W | Diffusive strobed dome illuminator - large size high power white |



LTDMLA series
High-power strobed LED dome + low angle lights

| | |
|--------------------|--|
| LTDMLAB2-WW | Diffusive strobed dome + low angle illumination system - medium size high power white |
| LTDMLAC1-WW | Diffusive strobed dome + low angle illumination system - large size medium power white |
| LTDMLAC2-WW | Diffusive strobed dome + low angle illumination system - large size high power white |

