

# TCCXQ016-W

Telecentric assembly with coaxial illumination for 2/3" detectors, magnification 0.16x, white

参数

光学说明书

放大	(x)	0.157
图像圈 Ø	(mm)	11
Object distance	(mm)	50.7

物体的视野

1/3" 探测器(4.8 x 3.6 毫米)	(mm x mm)	30.6 x 22.9
1/2" 探测器 (6.4 x 4.8 毫米)	(mm x mm)	40.8 x 30.6
1/1.8"探测器(7.13 x 5.37 毫米)	(mm x mm)	45.4 x 34.2
2/3"- 5 MP检测器(8.45 x 7.07毫米)	(mm x mm)	53.8 x 45.0

电性能指标

浅色,峰值波长		white
---------	--	-------

Device power ratings

DC voltage (min)	(V)	12
DC voltage (max)	(V)	24
Power consumption	(W)	< 2.5
Max LED fwd current 1	(mA)	350

LED power ratings

Forward voltage (typical) 2	(V)	2.78
Forward voltage (max) 2	(V)	-
Max pulse current 3	(mA)	2000

大小

接口		C
长度	(mm)	319.2
高度	(mm)	108
宽度	(mm)	336.7
重量	(g)	675

Eye safety

Risk group according to CEI EN 62471:2010		Risk group 1
---	--	--------------

注释


- Used in continuous (not pulsed) mode.
- At max forward current. Tolerance is ±0.06V on forward voltage measurements.
- At pulse width ≤ 10 ms, duty cycle ≤ 10% condition. Built-in electronics board must be bypassed (see tech info).

兼容产品




CMHO 系列  
夹具机构

CMHO056	机械固定架
---------	-------



连接器



Pinout reference

PIN	FUNCTION
1	Earth
2	GND
3	LED Anode
4	Power supply (+12+24 V)

