

TCCXQ075-G

Telecentric assembly with coaxial illumination for 2/3" detectors, magnification 0.75x, green

参数

光学说明书

放大	(x)	0.750
图像圈 Ø	(mm)	11
Object distance	(mm)	82.8

物体的视野

1/3" 探测器(4.8 x 3.6 毫米)	(mm x mm)	6.40 x 4.80
1/2" 探测器 (6.4 x 4.8 毫米)	(mm x mm)	8.53 x 6.4
1/1.8" 探测器(7.13 x 5.37 毫米)	(mm x mm)	9.51 x 7.16
2/3"- 5 MP 探测器(8.45 x 7.07毫米)	(mm x mm)	11.3 x 9.43

电性能指标

浅色,峰值波长	green, 520 nm	
---------	---------------	--

Device power ratings

DC voltage (min)	(V)	12
DC voltage (max)	(V)	24
Power consumption	(W)	< 2.5
Max LED fwd current 1	(mA)	350

LED power ratings

Forward voltage (typical) 2	(V)	3.3
Forward voltage (max) 2	(V)	4.00
Max pulse current 3	(mA)	2000

大小

接口	C	
长度	(mm)	155.0
高度	(mm)	64
宽度	(mm)	213.5
重量	(g)	1050

Eye safety

Risk group according to CEI EN 62471:2010	Risk group 1
---	--------------

注释

1. Used in continuous (not pulsed) mode.
2. At max forward current. Tolerance is ±0.06V on forward voltage measurements.
3. At pulse width ≤ 10 ms, duty cycle ≤ 10% condition. Built-in electronics board must be bypassed (see tech info).


兼容产品




CMHO 系列
夹具机构

CMHO016

机械固定架



连接器



Pinout reference

PIN	FUNCTION
1	Earth
2	GND
3	LED Anode
4	Power supply (+12÷24 V)

