

P71-78

最大支持1英寸(16.2mm) 靶面相机



最大支持1英寸(16.2mm)靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨率(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	2/3" 8.45x7.07 mm	1" 12.8x9.6 mm	1" 13.1x8.8 mm
XF-PTL03716-C-VI	0.441	110	36.7	16.2	0.03	3.7-17.9	F6.5-F31.3	9.7-46.82	160-33	0.03%	C	272.4	Ⅳ	19.16X16.03	29.02X21.77	29.71X19.95
XF-PTL04516-C-VI	0.359	120	45.1	16.2	0.03	5.6-27	F6.5-F31.3	11.9-57.47	160-33	0.024%	C	314.6	Ⅳ	23.54X19.69	35.65X26.74	36.49X24.51
XF-PTL05516-C	0.294	138	55.1	16.2	0.04	8.3	F6.5	14.6	160	0.031%	C	375.5	Ⅳ	28.74X24.05	43.54X32.65	44.56X29.93
XF-PTL06516-C	0.248	160	65.3	16.2	0.03	11.6	F6.5	17.3	160	0.017%	C	413.2	Ⅳ	34.07X28.51	51.61X38.71	52.82X35.48
XF-PTL08016-C	0.202	180	80.2	16.2	0.03	17.6	F6.5	21.22	160	0.019%	C	467.8	Ⅳ	41.83X35	63.37X47.52	64.85X43.56
XF-PTL09216-C	0.177	250	91.5	16.2	0.04	23.1	F6.5	24.3	160	0.019%	C	562.6	Ⅳ	47.74X39.94	72.32X54.24	74.01X49.72
XF-PTL11016-C	0.147	250	110.2	16.2	0.04	33.5	F6.5	29.2	160	0.020%	C	611.8	Ⅳ	57.48X48.1	87.07X65.31	89.12X59.86
XF-PTL12216-C	0.133	260	121.8	16.2	0.04	41.1	F6.5	32.4	160	0.026%	C	660.5	Ⅳ	63.53X53.16	96.24X72.18	98.5X66.17
XF-PTL13716-C	0.118	280	137.3	16.2	0.04	52.4	F6.5	36.4	160	0.038%	C	688.5	Ⅳ	71.61X59.92	108.47X81.36	111.02X74.58
XF-PTL15216-C	0.107	320	151.4	16.2	0.04	63.4	F6.5	40.23	160	0.039%	C	767.6	Ⅳ	78.97X66.07	119.63X89.72	122.43X82.24
XF-PTL18216-C	0.0888	398	182.4	16.2	0.04	91.2	F6.5	48.31	160	0.044%	C	893.5	Ⅳ	95.16X79.62	144.14X108.11	147.52X99.1
XF-PTL19516-C	0.083	400	195.2	16.2	0.04	104.3	F6.5	51.66	160	0.044%	C	921.9	Ⅳ	101.81X85.18	154.22X115.66	157.83X106.02
XF-PTL23816-C	0.0679	410	238.6	16.2	0.04	153.9	F6.5	63.2	160	0.025%	C	1080	Ⅳ	124.45X104.12	188.51X141.38	192.93X129.6
XF-PTL26816-C	0.0604	410	268.2	16.2	0.04	193.6	F6.5	71.0	160	0.050%	C	1138.6	Ⅳ	139.9X117.05	211.92X158.94	216.89X145.7
XF-PTL31016-C	0.0522	500	310.3	16.2	0.04	261.0	F6.5	82.2	160	0.041%	C	1294.9	Ⅳ	161.88X135.44	245.21X183.91	250.96X168.58
XF-PTL35016-C	0.0462	540	350.6	16.2	0.05	329.4	F6.5	92.8	160	0.041%	C	1407.1	Ⅳ	182.9X153.03	277.06X207.79	283.55X190.48
XF-PTL39016-C	0.0415	700	390.4	16.2	0.04	410.1	F6.5	103.4	160	0.044%	C	1787.4	Ⅳ	203.61X170.36	308.43X231.33	315.66X212.05
XF-10MDT08X178-1C	0.8	178	22.0	17.6	0.15	1.7	F10	8.3	100	0.100%	C	351.2	Ⅲ	10.56X8.84	16X12	16.38X11
XF-10MDT08X178D-1C	0.8	178	22.0	17.6	0.15	1.7	F10	8.3	100	0.100%	C	351.2	Ⅲ	10.56X8.84	16X12	16.38X11
XF-10MDT074X65-1C	0.74	65	23.8	17.6	0.26	1.7	F8.5	7.6	120	0.055%	C	217.1	Ⅲ	11.42X9.55	17.3X12.97	17.7X11.89
XF-10MDT074X65D-1C	0.74	65	23.8	17.6	0.28	1.7	F8.5	7.6	120	0.060%	C	220.1	Ⅲ	11.42X9.55	17.3X12.97	17.7X11.89
XF-10MDT06X80-1C	0.6	80	29.3	17.6	0.10	2.5	F8	8.8	125	0.021%	C	265.3	Ⅲ	14.08X11.78	21.33X16	21.83X14.67
XF-10MDT06X80D-1C	0.6	80	29.3	17.6	0.10	2.5	F8	8.8	125	0.079%	C	268.1	Ⅲ	14.08X11.78	21.33X16	21.83X14.67
XF-10MDT055X220-1C	0.55	220	32.0	17.6	0.09	2.9	F8	9.6	125	0.112%	C	455.2	Ⅲ	15.36X12.85	23.27X17.45	23.82X16
XF-10MDT05X110-1C	0.5	110	35.2	17.6	0.06	3.5	F8	10.5	125	0.162%	C	240	Ⅲ	16.9X14.14	25.6X19.2	26.2X17.6
XF-10MDT05X65-1C	0.5	65	35.2	17.6	0.38	2.7	F6	7.9	170	0.006%	C	216.1	Ⅲ	16.9X14.14	25.6X19.2	26.2X17.6
XF-10MDT05X65D-1C	0.5	65	35.2	17.6	0.39	2.7	F6	8	170	0.005%	C	218.9	Ⅲ	16.9X14.14	25.6X19.2	26.2X17.6
XF-10MDT05X220-1C	0.5	220	35.2	17.6	0.13	3.5	F8	10.6	125	0.095%	C	448	Ⅲ	16.9X14.14	25.6X19.2	26.2X17.6

- 最大可支持1"工业相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告

