

P41-46

最大支持2'(32mm) 靶面相机



最大支持2'(32mm)靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨力(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	7/4" 22.5x16.9mm	4k x 7μm 28.67mm	2" 23x23mm
XF-PTL03732-F-VI	0.896	110	36.3	32.5	0.03	1-5.9	F7.5-F42.2	5.5-31.1	135-25	0.040%	F	359.8	IV	25.11X18.86	32	25.67X25.67
XF-PTL04532-F-VI	0.73	120	44.5	32.5	0.03	1.6-8.8	F7.5-F42.2	6.8-38.2	135-25	0.039%	F	401.9	IV	30.82X23.15	39.27	31.51X31.51
XF-PTL05532-F-VI	0.597	138	54.4	32.5	0.04	1.9-13.2	F7.5-F42.2	8.3-46.7	135-25	0.060%	F	462.8	IV	37.69X28.31	48.02	38.53X38.53
XF-PTL06532-F-VI	0.505	160	64.4	32.5	0.03	3.3-18.5	F7.5-F42.2	9.8-55.2	135-25	0.034%	F	500.5	IV	44.55X33.47	56.77	45.54X45.54
XF-PTL08032-F-VI	0.411	180	79.1	32.5	0.03	5-28	F7.5-F42.2	12.1-67.9	135-25	0.037%	F	555.1	IV	54.74X41.12	69.76	55.96X55.96
XF-PTL09232-F-VI	0.359	250	90.5	32.5	0.04	6.4-36.5	F7.5-F42.2	13.8-77.7	135-25	0.038%	F	649.9	IV	62.67X47.08	79.86	64.07X64.07
XF-PTL11032-F	0.298	250	109.1	32.5	0.04	9.3	F7.5	16.6	135	0.036%	F	699.1	IV	75.5X56.71	96.21	77.18X77.18
XF-PTL12232-F	0.269	260	120.8	32.5	0.04	9.3	F7.5	18.4	135	0.042%	F	747.8	IV	83.64X62.83	106.58	85.5X85.5
XF-PTL13732-F	0.24	280	135.4	32.5	0.04	14.4	F7.5	20.7	135	0.051%	F	775.8	IV	93.75X70.42	119.46	95.83X95.83
XF-PTL15232-F	0.217	320	149.8	32.5	0.04	17.7	F7.5	22.85	135	0.053%	F	854.9	IV	103.69X77.88	132.12	105.99X105.99
XF-PTL18232-F	0.18	398	180.6	32.5	0.04	25.4	F7.5	27.43	135	0.057%	F	980.8	IV	125X93.89	159.28	127.78X127.78
XF-PTL19532-F	0.169	400	192.3	32.5	0.04	29.1	F7.5	29.34	135	0.057%	F	1009.2	IV	133.14X100	169.64	136.09X136.09
XF-PTL23832-F	0.138	410	235.5	32.5	0.04	43.3	F7.5	35.9	135	0.040%	F	1166.4	IV	163.04X122.46	207.75	166.67X166.67
XF-PTL26832-F	0.123	410	264.2	32.5	0.04	54.9	F7.5	40.34	135	0.053%	F	1225.8	IV	182.93X137.4	233.09	186.99X186.99
XF-PTL31032-F	0.106	500	306.6	32.5	0.04	73.2	F7.5	46.7	135	0.055%	F	1382.2	IV	212.26X159.43	270.47	216.98X216.98
XF-PTL35032-F	0.094	540	345.7	32.5	0.05	93.1	F7.5	52.7	135	0.055%	F	1494.4	IV	239.36X179.79	305	244.68X244.68
XF-PTL39032-F	0.084	700	386.9	32.5	0.04	115.9	F7.5	58.7	135	0.058%	F	1874.7	IV	267.86X201.19	341.31	273.81X273.81

- 最大可支持2"工业相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告