

P13-18

最大支持8K线扫 (57.4mm) 靶面相机



最大支持8K线扫 (57.4mm)靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨力(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	2" 23x23mm	8k x 5μm 40.96mm	35mm Full 36x24mm
XF-PTL03757-M72-11.48-VI	1.618	110	35.5	57.4	0.03	0.6@F15	F6-F76.6	6.13@F15	68@F15	0.045%	M72	460.3	IV	14.22X14.22	25.32	22.25X14.83
XF-PTL04557-M72-11.48-VI	1.319	120	43.5	57.4	0.03	0.7@F11	F6-F76.5	5.5@F11	95@F11	0.037%	M72	502.4	IV	17.44X17.44	31.05	27.29X18.2
XF-PTL05557-M72-11.48-VI	1.079	138	53.2	57.4	0.04	1@F11	F6-F76.5	6.7@F11	95@F11	0.017%	M72	563.4	IV	21.32X21.32	37.96	33.36X22.24
XF-PTL06557-M72-11.48-VI	0.912	160	62.9	57.4	0.03	1.5@F11	F6-F76.5	8@F11	95@F11	0.044%	M72	601	IV	25.22X25.22	44.91	39.47X26.32
XF-PTL08057-M72-11.48-VI	0.742	180	77.4	57.4	0.03	2.2@F11	F6-F76.5	9.8@F11	95@F11	0.035%	M72	655.7	IV	31X31	55.2	48.52X32.35
XF-PTL09257-M72-11.48-VI	0.648	250	88.6	57.4	0.04	2.9@F11	F6-F76	11.2@F11	95@F11	0.048%	M72	750.4	IV	35.49X35.49	63.21	55.56X37.04
XF-PTL11057-M72-11.48-VI	0.539	250	106.5	57.4	0.04	4.2@F11	F6-F76	13.5@F11	95@F11	0.043%	M72	799.6	IV	42.67X42.67	75.99	66.79X44.53
XF-PTL12257-M72-11.48-VI	0.486	260	118.1	57.4	0.04	5.1@F11	F6-F76	15@F11	95@F11	0.030%	M72	848.3	IV	47.33X47.33	84.28	74.07X49.38
XF-PTL13757-M72-11.48-VI	0.433	280	132.6	57.4	0.04	6.4@F11	F6-F76	16.8@F11	95@F11	0.034%	M72	876.3	IV	53.12X53.12	94.6	83.14X55.43
XF-PTL15257-M72-11.48-VI	0.391	320	146.8	57.4	0.04	7.9@F11	F6-F76	18.6@F11	95@F11	0.032%	M72	955.4	IV	58.82X58.82	104.76	92.07X61.38
XF-PTL18257-M72-11.48-VI	0.326	398	176.1	57.4	0.04	11.4@F11	F6-F76	22.3@F11	95@F11	0.033%	M72	1081.3	IV	70.55X70.55	125.64	110.43X73.62
XF-PTL19557-M72-11.48-VI	0.305	400	188.2	57.4	0.04	13.1@F11	F6-F76	23.8@F11	95@F11	0.032%	M72	1109.7	IV	75.41X75.41	134.3	118.03X78.69
XF-PTL23857-M72-11.48-VI	0.249	410	230.5	57.4	0.04	19.3@F11	F6-F76	29.1@F11	95@F11	0.028%	M72	1267.8	IV	92.37X92.37	164.5	144.58X96.39
XF-PTL26857-M72-11.48-VI	0.222	410	258.6	57.4	0.04	24.4@F11	F6-F76	32.8@F11	90@F11	0.032%	M72	1326.4	IV	103.6X103.6	184.5	162.16X108.11
XF-PTL31057-M72-11.48-VI	0.192	500	299.0	57.4	0.04	32.9@F11	F6-F76	37.9@F11	93@F11	0.027%	M72	1482.7	IV	119.79X119.79	213.33	187.5X125
XF-PTL35057-M72-11.48-VI	0.17	540	337.6	57.4	0.05	41.7@F11	F6-F76	42.8@F11	95@F11	0.026%	M72	1594.9	IV	135.29X135.29	240.94	211.76X141.18
XF-PTL39057-M72-11.48-VI	0.152	700	377.6	57.4	0.04	52.1@F11	F6-F76	47.7@F11	95@F11	0.028%	M72	1975.2	IV	151.32X151.32	269.47	236.84X157.89

- 最大可支持8K线扫描相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告