

P07-12

最大支持12K线扫 (62mm) 靶面相机



最大支持12K线扫(62mm)靶面相机参数

镜头型号	倍率 (X)	工作距离 (mm)	物方视野 (mm)	像方视野 (mm)	远心设计值 (°)	景深 (mm)	光圈	分辨率 (μm)	像方MTF30 (LP/mm)	光学畸变设计值 (%)	镜头接口	O/I	第几代产品	8k x 5μm 40.96 mm	35mm Full 36x24 mm	12k x 5μm 61.44mm
XF-PTL03762-M72-11.48-VI	1.755	110	35.3	62	0.03	0.5@F15	F6-F83	5.7@F15	68@F15	0.036%	M72	471.2	IV	23.34	20.51X13.68	35.01
XF-PTL04562-M72-11.48-VI	1.43	120	43.4	62	0.03	0.8@F15	F6-F83	6.9@F15	68@F15	0.029%	M72	513.3	IV	28.64	25.17X16.78	42.97
XF-PTL05562-M72-11.48-VI	1.17	138	53.0	62	0.04	1.2@F15	F6-F83	8.5@F15	68@F15	0.012%	M72	574.3	IV	35.01	30.77X20.51	52.51
XF-PTL06562-M72-11.48-VI	0.989	160	62.7	62	0.03	1.2@F11	F6-F83	7.4@F11	95@F11	0.037%	M72	611.9	IV	41.42	36.4X24.27	62.12
XF-PTL08062-M72-11.48-VI	0.805	180	77.0	62	0.03	1.8@F11	F6-F83	9.0@F11	95@F11	0.028%	M72	666.3	IV	50.88	44.72X29.81	76.32
XF-PTL09262-M72-11.48-VI	0.702	250	88.3	62	0.04	2.4@F11	F6-F83	10.3@F11	95@F11	0.043%	M72	761.3	IV	58.35	51.28X34.19	87.52
XF-PTL11062-M72-11.48-VI	0.584	250	106.2	62	0.04	3.5@F11	F6-F83	12.4@F11	95@F11	0.038%	M72	810.5	IV	70.14	61.64X41.1	105.21
XF-PTL12262-M72-11.48-VI	0.527	260	117.6	62	0.04	4.2@F11	F6-F83	13.8@F11	95@F11	0.022%	M72	859.2	IV	77.72	68.31X45.54	116.58
XF-PTL13762-M72-11.48-VI	0.47	280	131.9	62	0.04	5.3@F11	F6-F83	15.5@F11	95@F11	0.025%	M72	887.2	IV	87.15	76.6X51.06	130.72
XF-PTL15262-M72-11.48-VI	0.424	320	146.2	62	0.04	6.6@F11	F6-F83	17.1@F11	95@F11	0.022%	M72	966.3	IV	96.6	84.91X56.6	144.91
XF-PTL18262-M72-11.48-VI	0.353	398	175.6	62	0.04	9.6@F11	F6-F83	20.5@F11	95@F11	0.025%	M72	1092.2	IV	116.03	101.98X67.99	174.05
XF-PTL19562-M72-11.48-VI	0.331	400	187.3	62	0.04	11.1@F11	F6-F83	22@F11	95@F11	0.023%	M72	1120.6	IV	123.75	108.76X72.51	185.62
XF-PTL23862-M72-11.48-VI	0.27	410	229.6	62	0.04	16.5@F11	F6-F83	26.9@F11	95@F11	0.018%	M72	1278.7	IV	151.7	133.33X88.89	227.56
XF-PTL26862-M72-11.48-VI	0.24	410	258.3	62	0.04	20.8@F11	F6-F83	30.2@F11	90@F11	0.023%	M72	1337.3	IV	170.67	150X100	256
XF-PTL31062-M72-11.48-VI	0.208	500	298.1	62	0.04	28.2@F11	F6-F83	35@F11	93@F11	0.018%	M72	1493.6	IV	196.92	173.08X115.38	295.38
XF-PTL35062-M72-11.48-VI	0.184	540	337.0	62	0.05	35.7@F11	F6-F83	39.4@F11	95@F11	0.016%	M72	1605.8	IV	222.61	195.65X130.43	333.91
XF-PTL39062-M72-11.48-VI	0.165	700	375.8	62	0.04	44.4@F11	F6-F83	44@F11	95@F11	0.020%	M72	1986.2	IV	248.24	218.18X145.45	372.36

- 最大可支持12K线扫描相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告