

P01-06

最大支持16K线扫 (82mm) 靶面相机



最大支持16K线扫(82mm) 靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨力(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	8k x 5μm 40.96mm	35mm Full 36x24mm	16k x 5μm 81.92mm
XF-PTL04582-M95-12-VI	1.92	120	42.7	82	0.03	0.5@F18	F8-F111.5	6.20@F18	58@F18	0.034%	M95接口	604.4	IV	21.33	18.75X12.5	42.67
XF-PTL05582-M95-12-VI	1.571	138	52.2	82	0.04	0.8@F18	F8-F111.5	7.57@F18	58@F18	0.054%	M95接口	665.4	IV	26.07	22.92X15.28	52.15
XF-PTL06582-M95-12-VI	1.328	160	61.7	82	0.03	0.8@F13.5	F8-F111.5	6.7@F13.5	75@F13.5	0.028%	M95接口	703	IV	30.84	27.11X18.07	61.69
XF-PTL08082-M95-12-VI	1.08	180	75.9	82	0.03	1.2@F13.5	F8-F111	8.3@F13.5	75@F13.5	0.031%	M95接口	757.7	IV	37.93	33.33X22.22	75.85
XF-PTL09282-M95-12-VI	0.943	250	87.0	82	0.04	1.5@F13.5	F8-F111	9.5@F13.5	75@F13.5	0.032%	M95接口	852.4	IV	43.44	38.18X25.45	86.87
XF-PTL11082-M95-12-VI	0.785	250	104.5	82	0.04	2.2@F13.5	F8-F111	11.3@F13.5	75@F13.5	0.030%	M95接口	901.6	IV	52.18	45.86X30.57	104.36
XF-PTL12282-M95-12-VI	0.708	260	115.8	82	0.04	2.7@F13.5	F8-F111	12.6@F13.5	75@F13.5	0.035%	M95接口	950.3	IV	57.85	50.85X33.9	115.71
XF-PTL13782-M95-12-VI	0.631	280	130.0	82	0.04	3.4@F13.5	F8-F111	14.1@F13.5	75@F13.5	0.039%	M95接口	978.3	IV	64.91	57.05X38.03	129.83
XF-PTL15282-M95-12-VI	0.57	320	143.9	82	0.04	4.3@F13.5	F8-F111	15.6@F13.5	75@F13.5	0.040%	M95接口	1057.4	IV	71.86	63.16X42.11	143.72
XF-PTL18282-M95-12-VI	0.475	398	172.6	82	0.04	6.2@F13.5	F8-F111	18.8@F13.5	75@F13.5	0.043%	M95接口	1183.3	IV	86.23	75.79X50.53	172.46
XF-PTL19582-M95-12-VI	0.444	400	184.7	82	0.04	7.3@F13.5	F8-F111	20.1@F13.5	75@F13.5	0.042%	M95接口	1211.8	IV	92.25	81.08X54.05	184.5
XF-PTL23882-M95-12-VI	0.363	410	225.9	82	0.04	11.3@F13.5	F8-F111	24.5@F13.5	75@F13.5	0.034%	M95接口	1369.8	IV	112.84	99.17X66.12	225.67
XF-PTL26882-M95-12-VI	0.323	410	253.9	82	0.04	14@F13.5	F8-F111	27.6@F13.5	75@F13.5	0.040%	M95接口	1428.4	IV	126.81	111.46X74.3	253.62
XF-PTL31082-M95-12-VI	0.279	500	293.9	82	0.04	19.2@F13.5	F8-F111	31.9@F13.5	75@F13.5	0.041%	M95接口	1584.7	IV	146.81	129.03X86.02	293.62
XF-PTL35082-M95-12-VI	0.247	540	332.0	82	0.05	24.3@F13.5	F8-F111	36.1@F13.5	75@F13.5	0.043%	M95接口	1697	IV	165.83	145.75X97.17	331.66
XF-PTL39082-M95-12-VI	0.222	700	369.4	82	0.04	29.3@F13.5	F8-F111	40.2@F13.5	75@F13.5	0.045%	M95接口	2077.3	IV	184.5	162.16X108.11	369.01

- 最大可支持16K线扫描相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告