

P103-108

标准分辨率远心镜头 (WD:65mm)



标准分辨率远心镜头(WD:65mm)参数



镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨率(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	1/3" 4.8x3.6mm	1/2" 6.4x4.8mm	2/3" 8.45x7.07mm
XF-T2X40	2	40	4	8	0.21	0.91	F33.2	11	32	0.090%	C	111.8	I	2.4X1.8	3.2X2.4	/
XF-T2X40D	2	40	4	8	0.11	0.89	F33.3	11	32	0.190%	C	115.5	I	2.4X1.8	3.2X2.4	/
XF-T03X65	0.3	65	20	6	0.2	14.8	F15	33	70	0.240%	C	170.9	/	16X12	/	/
XF-T03X65D	0.3	65	20	6	0.20	14.8	F15	33	70	0.240%	C	173.4	/	16X12	/	/
XF-T05X65	0.5	65	22	11	0.26	7.2	F16.7	22	60	0.001%	C	184.6	II	9.6X7.2	12.8X9.6	16.9X14.14
XF-T05X65D	0.5	65	22	11	0.25	7.3	F16.5	22	60	0.008%	C	187.6	II	9.6X7.2	12.8X9.6	16.9X14.14
XF-T08X65-Y11	0.8	65	10	8	0.2	2.6	F16	13.2	65	0.230%	C	175.8	/	6X4.5	8X6	/
XF-T08X65	0.8	65	13.8	11	0.08	2.5	F14.8	12.2	70	0.085%	C	180.8	II	6X4.5	8X6	10.56X8.84
XF-T08X65D	0.8	65	13.8	11	0.07	2.5	F14.8	12.2	70	0.085%	C	183.9	II	6X4.5	8X6	10.56X8.84
XF-T1X65D-Y11	1	65	8	8	0.5	1.8	F16.7	11	60	0.086%	C	177.7	I	4.8X3.6	6.4X4.8	/
XF-T1X65-Y11	1	65	8	8	0.22	1.8	F16.7	11	60	0.085%	C	174.6	I	4.8X3.6	6.4X4.8	/
XF-T1X65	1	65	11	11	0.06	1.8	F16.6	11	60	0.040%	C	190.1	II	4.8X3.6	6.4X4.8	8.45X7.07
XF-T1X65D	1	65	11	11	0.06	1.8	F16.6	11	60	0.040%	C	193.1	II	4.8X3.6	6.4X4.8	8.45X7.07
XF-T2X65	2	65	4	8	0.08	0.47	F17.4	5.8	55	0.025%	C	150.4	I	2.4X1.8	3.2X2.4	/
XF-T2X65D	2	65	4	8	0.08	0.47	F17.4	5.8	50	0.035%	C	153.6	I	2.4X1.8	3.2X2.4	/
XF-T3X65	3	65	2.7	8	0.16	0.28	F24.9	5.5	40	0.130%	C	150.4	I	1.6X1.2	2.13X1.6	/
XF-T3X65D	3	65	2.7	8	0.04	0.27	F24.9	5.5	40	0.130%	C	153.6	I	1.6X1.2	2.13X1.6	/
XF-T4X65	4	65	2	8	0.02	0.13	F26.2	4.3	35	0.122%	C	185.2	I	1.2X0.9	1.6X1.2	/
XF-T4X65D	4	65	2	8	0.02	0.15	F27.3	4.5	35	0.053%	C	188.4	I	1.2X0.9	1.6X1.2	/
XF-T6X65 (无景深)	6	65	1.3	8	0.02	/	F39.3	4.3	23	0.040%	C	203.9	I	0.8X0.6	1.07X0.8	/
XF-T6X65D	6	65	1.3	8	0.02	0.06	F39.4	4.3	23	0.039%	C	207.3	I	0.8X0.6	1.07X0.8	/
XF-T8X65 (无景深)	8	65	1	8	0.01	/	F52.4	4.3	18	0.028%	C	223.8	I	0.6X0.45	0.8X0.6	/
XF-T8X65D (无景深)	8	65	1	8	0.01	/	F52.4	4.3	17	0.026%	C	227.7	I	0.6X0.45	0.8X0.6	/

- 采用物方远心设计, 保证测量精准性
- 更短的工作距离为需要安装在狭小空间的场景带来了便利
- 倍率从0.3-8倍均可以覆盖, 全系列带有同轴光源版本
- 最大支持2/3英寸C接口工业相机
- 可应用于高精度工件定位等