

P23-28

最大支持全画幅(43.6mm) 靶面相机



最大支持全画幅(43.6)靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨力(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	4k x 7μm 28.67mm	8k x 5μm 40.96mm	35mm Full 36x24mm
XF-PTL03744-M58-11.48-VI	1.213	110	35.9	43.6	0.03	1.0-4.3	F13.5-F57.4	7.35-31.22	75-18	0.058%	M58	404.4	IV	23.64	33.77	29.68X19.79
XF-PTL04544-M58-11.48-VI	0.988	120	44.1	43.6	0.03	1-6.5	F9-F57.4	6-38.32	115-18	0.050%	M58	446.5	IV	29.02	41.46	36.44X24.29
XF-PTL05544-M58-11.48-VI	0.809	138	53.9	43.6	0.04	1.5-9.8	F9-F57.4	7.4-46.82	115-18	0.019%	M58	507.5	IV	35.44	50.63	44.5X29.67
XF-PTL06544-M58-11.48-VI	0.684	160	63.7	43.6	0.03	2.1-13.7	F9-F57.4	8.7-55.41	115-18	0.048%	M58	545.1	IV	41.92	59.88	52.63X35.09
XF-PTL08044-M58-11.48-VI	0.556	180	78.4	43.6	0.03	3.2-20.7	F9-F57	10.7-68.1	115-18	0.045%	M58	599.7	IV	51.56	73.67	64.75X43.17
XF-PTL09244-M58-11.48-VI	0.486	250	89.7	43.6	0.04	4.1-27.1	F9-F57	12.2-77.7	115-18	0.050%	M58	694.5	IV	58.99	84.28	74.07X49.38
XF-PTL11044-M58-11.48-VI	0.404	250	107.9	43.6	0.04	6-39	F9-F57	14.7-93.4	115-18	0.050%	M58	743.7	IV	70.97	101.39	89.11X59.41
XF-PTL12244-M58-11.48-VI	0.365	260	119.5	43.6	0.04	7.3-47.4	F9-F57	16.3-103.1	115-18	0.042%	M58	792.4	IV	78.55	112.22	98.63X65.75
XF-PTL13744-M58-11.48-VI	0.325	280	134.2	43.6	0.04	9.2-59.4	F9-F57	18.3-117.9	115-18	0.048%	M58	820.4	IV	88.22	126.03	110.77X73.85
XF-PTL15244-M58-11.48	0.293	320	148.8	43.6	0.04	11.3	F9	20.25	115	0.045%	M58	899.5	IV	97.85	139.8	122.87X81.91
XF-PTL18244-M58-11.48	0.244	398	178.7	43.6	0.04	16.3	F9	24.44	115	0.047%	M58	1025.4	IV	117.5	167.87	147.54X98.36
XF-PTL19544-M58-11.48	0.229	400	190.4	43.6	0.04	18.7	F9	26.00	115	0.046%	M58	1054.1	IV	125.2	178.86	157.21X104.8
XF-PTL23844-M58-11.48	0.187	410	233.2	43.6	0.04	28.0	F9	31.8	115	0.040%	M58	1211.9	IV	153.32	219.04	192.51X128.34
XF-PTL26844-M58-11.48	0.166	410	262.7	43.6	0.04	35.5	F9	35.8	115	0.050%	M58	1270.5	IV	172.71	246.75	216.87X144.58
XF-PTL31044-M58-11.48	0.144	500	302.8	43.6	0.04	47.5	F9	41.4	115	0.043%	M58	1426.8	IV	199.1	284.44	250X166.67
XF-PTL35044-M58-11.48	0.127	540	343.3	43.6	0.05	60.4	F9	46.7	115	0.040%	M58	1539	IV	225.75	322.52	283.46X188.98
XF-PTL39044-M58-11.48	0.114	700	382.5	43.6	0.04	74.8	F9	52.1	115	0.045%	M58	1919.3	IV	251.49	359.3	315.79X210.53

- 最大可支持全画幅工业相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告