

P79-84

最大支持2/3英寸(11mm) 靶面相机



最大支持2/3英寸(11mm)靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨力(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	1/2" 6.4x4.8mm	1/1.8" 7.2x5.3mm	2/3" 8.45x7.07mm
XF-PTL03711-C-VI	0.3	110	36.7	11	0.03	8-26.2	F6.5-F21.3	14.3-46.82	160-49	0.076%	C	249.2	IV	21.33X16	24X17.67	28.17X23.57
XF-PTL04511-C	0.244	120	45.1	11	0.03	14.8	F8	21.60	130	0.070%	C	291.4	IV	26.23X19.67	29.51X21.72	34.63X28.98
XF-PTL05511-C	0.2	138	55.0	11	0.04	22.0	F8	26.40	130	0.036%	C	352.3	IV	32X24	36X26.5	42.25X35.35
XF-PTL06511-C	0.169	160	65.1	11	0.03	30.8	F8	31.2	130	0.062%	C	390	IV	37.87X28.4	42.6X31.36	50X41.83
XF-PTL08011-C	0.138	180	79.7	11	0.03	46.5	F8	38.39	130	0.062%	C	444.6	IV	46.38X34.78	52.17X38.41	61.23X51.23
XF-PTL09211-C	0.12	250	91.7	11	0.04	60.9	F8	44.0	130	0.065%	C	539.4	IV	53.33X40	60X44.17	70.42X58.92
XF-PTL11011-C	0.1	250	110.0	11	0.04	88.2	F8	52.9	130	0.065%	C	588.6	IV	64X48	72X53	84.5X70.7
XF-PTL12211-C	0.09	260	122.2	11	0.04	108.1	F8	58.6	130	0.060%	C	637.3	IV	71.11X53.33	80X58.89	93.89X78.56
XF-PTL13711-C	0.08	280	137.5	11	0.04	136.2	F8	66.00	130	0.070%	C	665.3	IV	80X60	90X66.25	105.63X88.38
XF-PTL15211-C	0.0725	320	151.7	11	0.04	166.7	F8	72.78	130	0.066%	C	744.4	IV	88.28X66.21	99.31X73.1	116.55X97.52
XF-PTL18211-C	0.06	398	183.3	11	0.04	238.9	F8	87.53	130	0.068%	C	870.3	IV	106.67X80	120X88.33	140.83X117.83
XF-PTL19511-C	0.0565	400	194.7	11	0.04	273.0	F8	93.46	130	0.070%	C	898.7	IV	113.27X84.96	127.43X93.81	149.56X125.13
XF-PTL23811-C	0.0462	410	238.1	11	0.04	392.8	F8	114.2	130	0.060%	C	1056.8	IV	138.53X103.9	155.84X114.72	182.9X153.03
XF-PTL26811-C	0.0411	410	267.6	11	0.04	484.6	F8	128.5	130	0.072%	C	1115.4	IV	155.72X116.79	175.18X128.95	205.6X172.02
XF-PTL31011-C	0.0355	500	309.9	11	0.04	666.1	F8	148.7	130	0.065%	C	1271.7	IV	180.28X135.21	202.82X149.3	238.03X199.15
XF-PTL35011-C	0.0315	540	349.2	11	0.05	817.6	F8	167.8	130	0.065%	C	1383.9	IV	203.17X152.38	228.57X168.25	268.25X224.44
XF-PTL39011-C	0.0282	700	390.1	11	0.04	1028.8	F8	187.5	130	0.065%	C	1764.2	IV	226.95X170.21	255.32X187.94	299.65X250.71
XF-5MDT05X65D	0.5	65	22	11	0.25	2.7	F6	8	175	0.008%	C	187.6	II	12.8X9.6	14.4X10.6	16.9X14.14
XF-5MDT05X65	0.5	65	22	11	0.26	2.7	F6	7.9	175	0.001%	C	184.6	II	12.8X9.6	14.4X10.6	16.9X14.14
XF-5MDT05X178D	0.5	178	22	11	0.12	3.1	F7	9.3	150	0.043%	C	414.1	III	12.8X9.6	14.4X10.6	16.9X14.14
XF-5MDT05X178	0.5	178	22	11	0.12	3.1	F7	9.2	150	0.042%	C	411.5	III	12.8X9.6	14.4X10.6	16.9X14.14
XF-5MDTE04X110B	0.4	110	27.5	11	0.1	6.8	F10	16.5	100	0.019%	C	266.6	III	16X12	18X13.25	21.13X17.68
XF-5MDTE03X65	0.3	65	36.7	11	0.05	12.5	F10	22.0	105	0.043%	C	196.9	III	21.33X16	24X17.67	28.17X23.57

- 最大可支持2/3"工业相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告
- 可应用于玻璃盖板灰尘检查等