

P53-58

最大支持4/3'(23mm) 靶面相机



最大支持4/3'(23mm)靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨力(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	1.1" 14.2x10.4 mm	2k x 10μm 20.48mm	4/3" 18x13.5 mm
XF-PTL03723-C-VI	0.634	110	36.3	23	0.03	1.8-12.5	F6.5-F45	6.8-46.82	160-23	0.023%	C	309.5	IV	22.4X16.4	32.3	28.39X21.29
XF-PTL04523-C-VI	0.516	120	44.6	23	0.03	2.7-18.8	F6.5-F45	8.3-57.47	160-23	0.017%	C	351.6	IV	27.52X20.16	39.69	34.88X26.16
XF-PTL05523-C-VI	0.422	138	54.5	23	0.04	4-28	F6.5-F45	10.2-70.23	160-23	0.026%	C	412.6	IV	33.65X24.64	48.53	42.65X31.99
XF-PTL06523-C-VI	0.357	160	64.4	23	0.03	5.6-39.2	F6.5-F45	12-83.11	160-23	0.013%	C	450.3	IV	39.78X29.13	57.37	50.42X37.82
XF-PTL08023-C	0.29	180	79.3	23	0.03	10.5	F8	18.18	130	0.013%	C	504.9	IV	48.97X35.86	70.62	62.07X46.55
XF-PTL09223-C	0.254	250	90.6	23	0.04	13.7	F8	20.8	130	0.017%	C	599.6	IV	55.91X40.94	80.63	70.87X53.15
XF-PTL11023-C	0.211	250	109.0	23	0.04	19.8	F8	25.0	130	0.015%	C	648.9	IV	67.3X49.29	97.06	85.31X63.98
XF-PTL12223-C	0.19	260	121.1	23	0.04	24.4	F8	27.7	130	0.019%	C	697.5	IV	74.74X54.74	107.79	94.74X71.05
XF-PTL13723-C	0.17	280	135.3	23	0.04	30.8	F8	31.1	130	0.031%	C	725.6	IV	83.53X61.18	120.47	105.88X79.41
XF-PTL15223-C	0.153	320	150.3	23	0.04	37.6	F8	34.46	130	0.033%	C	804.6	IV	92.81X67.97	133.86	117.65X88.24
XF-PTL18223-C	0.128	398	179.7	23	0.04	54.1	F8	41.41	130	0.038%	C	930.5	IV	110.94X81.25	160	140.63X105.47
XF-PTL19523-C	0.119	400	193.3	23	0.04	61.9	F8	44.25	130	0.038%	C	959	IV	119.33X87.39	172.1	151.26X113.45
XF-PTL23823-C	0.0976	410	235.7	23	0.04	91.5	F8	54.10	130	0.019%	C	1117	IV	145.49X106.56	209.84	184.43X138.32
XF-PTL26823-C	0.0868	410	265.0	23	0.04	115.5	F8	60.9	130	0.035%	C	1175.6	IV	163.59X119.82	235.94	207.37X155.53
XF-PTL31023-C	0.075	500	306.7	23	0.04	155.4	F8	70.4	130	0.035%	C	1332	IV	189.33X138.67	273.07	240X180
XF-PTL35023-C	0.0664	540	346.4	23	0.05	196.8	F8	79.5	130	0.036%	C	1444.2	IV	213.86X156.63	308.43	271.08X203.31
XF-PTL39023-C	0.0596	700	385.9	23	0.04	244.7	F8	88.7	130	0.037%	C	1824.5	IV	238.26X174.5	343.62	302.01X226.51

- 最大可支持4/3"工业相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告
- 高精度工件检测及机器视觉应用