

P47-52

最大支持7/4' & 4K线扫(28mm)靶面相机



最大支持7/4' & 4K线扫(28mm)靶面相机参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨力(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	4/3" 18x13.5 mm	7/4" 22.5x16.9 mm	4k x 7μm 28.67mm
XF-PTL03729-F-VI	0.793	110	36.6	29	0.03	1.2-6.6	F7-F37.5	5.8-31.22	145-27	0.052%	F	335.7	IV	22.7X17.02	28.37X21.31	36.15
XF-PTL04529-F-VI	0.646	120	44.9	29	0.03	1.8-10	F7-F37.5	7.2-38.32	145-27	0.046%	F	377.8	IV	27.86X20.9	34.83X26.16	44.38
XF-PTL05529-F-VI	0.528	138	54.9	29	0.04	2.7-15	F7-F37.5	8.7-46.82	145-27	0.012%	F	438.7	IV	34.09X25.57	42.61X32.01	54.3
XF-PTL06529-F-VI	0.447	160	64.9	29	0.03	3.8-20.9	F7-F37.5	10.4-55.41	145-27	0.040%	F	476.4	IV	40.27X30.2	50.34X37.81	64.14
XF-PTL08029-F-VI	0.363	180	79.9	29	0.04	5.8-31.6	F7-F37.5	12.7-68.1	145-27	0.039%	F	531	IV	49.59X37.19	61.98X46.56	78.98
XF-PTL09229-F-VI	0.317	250	91.5	29	0.04	7.6-41.1	F7-F37.5	14.6-78	145-27	0.041%	F	625.8	IV	56.78X42.59	70.98X53.31	90.44
XF-PTL11029-F	0.264	250	109.8	29	0.04	11.0	F7	17.50	145	0.043%	F	675	IV	68.18X51.14	85.23X64.02	108.6
XF-PTL12229-F	0.238	260	121.8	29	0.04	13.5	F7	19.4	145	0.038%	F	723.7	IV	75.63X56.72	94.54X71.01	120.46
XF-PTL13729-F	0.212	280	136.8	29	0.04	17.1	F7	21.8	145	0.045%	F	751.7	IV	84.91X63.68	106.13X79.72	135.24
XF-PTL15229-F	0.192	320	151.0	29	0.04	20.9	F7	24.1	145	0.042%	F	830.8	IV	93.75X70.31	117.19X88.02	149.32
XF-PTL18229-F	0.16	398	181.3	29	0.04	30.1	F7	28.94	145	0.044%	F	956.7	IV	112.5X84.38	140.63X105.63	179.19
XF-PTL19529-F	0.149	400	194.6	29	0.04	34.5	F7	30.95	145	0.043%	F	985.1	IV	120.81X90.6	151.01X113.42	192.42
XF-PTL23829-F	0.122	410	237.7	29	0.04	51.0	F7	37.8	145	0.037%	F	1143.2	IV	147.54X110.66	184.43X138.52	235
XF-PTL26829-F	0.109	410	266.1	29	0.04	64.6	F7	42.6	145	0.048%	F	1201.8	IV	165.14X123.85	206.42X155.05	263.03
XF-PTL31029-F	0.0938	500	309.2	29	0.04	86.8	F7	49.3	145	0.040%	F	1358.1	IV	191.9X143.92	239.87X180.17	305.65
XF-PTL35029-F	0.0831	540	349.0	29	0.05	110.4	F7	55.6	145	0.039%	F	1470.3	IV	216.61X162.45	270.76X203.37	345.01
XF-PTL39029-F	0.0746	700	388.7	29	0.04	137.5	F6.5	62.0	145	0.041%	F	1850.6	IV	241.29X180.97	301.61X226.54	384.32

- 最大可支持7/4"面阵工业相机或4K线扫描相机
- 双侧远心设计，超高远心度，可提升数倍的测量精度
- 可选配可变光阑，有效平衡景深与分辨率
- 可提供专门匹配的平行光源，提高照明均匀性
- 部分镜头支持内部L90转向，节约安装空间
- 该系列镜头均经过精密校准，可提供全面测试报告

