

P109-114

标准分辨率远心镜头 (WD:110mm)



标准分辨率远心镜头(WD:110mm)参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨率(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	1/3" 4.8x3.6mm	1/2" 6.4x4.8mm	2/3" 8.45x7.07mm
XF-T03X110	0.3	110	26.7	8	0.03	18.1	F15	33	65	0.310%	C	261.5	I	16X12	21.33X16	/
XF-T03X110D	0.3	110	26.7	8	0.03	18.1	F15	33	65	0.800%	C	264.6	I	16X12	21.33X16	/
XF-T05X110	0.5	110	16	8	0.12	7.0	F16.6	22	60	0.170%	C	233.8	I	9.6X7.2	12.8X9.6	/
XF-T05X110D	0.5	110	16	8	0.17	7.1	F16.7	22	60	0.140%	C	237.1	I	9.6X7.2	12.8X9.6	/
XF-T08X110-Y11	0.8	110	10	8	0.53	3.4	F20	16.5	50	0.077%	C	232.5	I	6X4.5	8X6	/
XF-T08X110D-Y11	0.8	110	10	8	0.73	3.3	F20	16.5	50	0.061%	C	235	I	6X4.5	8X6	/
XF-T08X110	0.8	110	13.8	11	0.08	2.9	F16.7	13.8	60	0.012%	C	244.7	II	6X4.5	8X6	10.56X8.84
XF-T08X110D	0.8	110	13.8	11	0.08	2.9	F16.7	13.8	60	0.012%	C	247.6	II	6X4.5	8X6	10.56X8.84
XF-T1X110-Y11	1	110	8	8	0.6	2.3	F20.8	13.8	50	0.063%	C	229.8	I	4.8X3.6	6.4X4.8	/
XF-T1X110D-Y11	1	110	8	8	0.6	2.3	F20.8	13.8	50	0.054%	C	233.1	I	4.8X3.6	6.4X4.8	/
XF-T1X110	1	110	11	11	0.07	2.3	F20.8	13.8	50	0.030%	C	254.3	II	4.8X3.6	6.4X4.8	8.45X7.07
XF-T1X110D	1	110	11	11	0.07	2.3	F20.8	13.8	50	0.032%	C	257	II	4.8X3.6	6.4X4.8	8.45X7.07
XF-T2X110	2	110	4	8	0.16	0.52	F22.1	7.3	40	0.300%	C	209.5	I	2.4X1.8	3.2X2.4	/
XF-T2X110D	2	110	4	8	0.16	0.50	F22.2	7.3	40	0.300%	C	212.8	I	2.4X1.8	3.2X2.4	/
XF-T3X110	3	110	2.7	8	0.11	0.24	F27.1	6	30	0.130%	C	235.1	I	1.6X1.2	2.13X1.6	/
XF-T3X110D	3	110	2.7	8	0.11	0.25	F27.2	6	30	0.130%	C	237.8	I	1.6X1.2	2.13X1.6	/
XF-T4X110	4	110	2	8	0.08	0.23	F44.3	7.3	22	0.330%	C	216.4	I	1.2X0.9	1.6X1.2	/
XF-T4X110D	4	110	2	8	0.001	0.22	F44.1	7.3	22	0.300%	C	219.6	I	1.2X0.9	1.6X1.2	/
XF-T6X110	6	110	1.3	8	0.05	0.15	F66.1	7.3	15	0.070%	C	233.1	I	0.8X0.6	1.07X0.8	/
XF-T6X110D	6	110	1.3	8	0.001	0.13	F66.1	7.3	15	0.064%	C	236.7	I	0.8X0.6	1.07X0.8	/

- 采用物方远心设计，提高测量精度
- 相比同系列具有更短的o/I距离，极大地丰富了应用场景
- 倍率从0.3-6倍均可以覆盖，全系列带有同轴光源版本
- 最大支持2/3 英寸C接口工业相机
- 可应用于高精度特殊工件定位等