

# P91-96

## 高分辨率远心镜头 (WD:65mm)



高分辨率远心镜头(WD:65MM)参数

镜头型号	倍率(X)	工作距离(mm)	物方视野(mm)	像方视野(mm)	远心设计值(°)	景深(mm)	光圈	分辨率(μm)	像方MTF30(LP/mm)	光学畸变设计值(%)	镜头接口	O/I	第几代产品	1/3" 4.8x3.6mm	1/2" 6.4x4.8mm	2/3" 8.45x7.07mm
XF-MT05X65D	0.5	65	22	11	0.25	4.3	F9.6	12.8	110	0.008%	C	187.6	II	9.6X7.2	12.8X9.6	16.9X14.14
XF-MT05X65	0.5	65	22	11	0.26	4.2	F9.6	12.7	110	0.001%	C	184.6	II	9.6X7.2	12.8X9.6	16.9X14.14
XF-MT08X65	0.8	65	13.8	11	0.08	1.7	F10	8.3	100	0.086%	C	180.8	II	6X4.5	8X6	10.56X8.84
XF-MT08X65D	0.8	65	13.8	11	0.07	1.7	F10	8.3	100	0.083%	C	183.9	II	6X4.5	8X6	10.56X8.84
XF-MT1X65	1	65	11	11	0.06	1.2	F11.1	7.3	90	0.038%	C	190.1	II	4.8X3.6	6.4X4.8	8.45X7.07
XF-MT1X65D	1	65	11	11	0.06	1.2	F11.1	7.3	90	0.039%	C	193.1	II	4.8X3.6	6.4X4.8	8.45X7.07
XF-MT1.5X65D	1.5	65	7.3	11	0.15	0.55	F11.9	5.2	85	0.105%	C	168.6	III	3.2X2.4	4.27X3.2	5.63X4.71
XF-MT1.5X65	1.5	65	7.3	11	0.15	0.55	F11.9	5.2	85	0.105%	C	168.6	III	3.2X2.4	4.27X3.2	5.63X4.71
XF-MT2X65D	2.14	65	5.1	11	0.11	0.35	F14.4	4.5	70	0.041%	C	170.7	III	2.24X1.68	2.99X2.24	3.95X3.3
XF-MT2X65	2.14	65	5.1	11	0.11	0.35	F14.4	4.5	70	0.041%	C	170.7	III	2.24X1.68	2.99X2.24	3.95X3.3
XF-MT3X65D	3	65	3.7	11	0.15	0.19	F15.7	3.5	65	0.038%	C	182	III	1.6X1.2	2.13X1.6	2.82X2.36
XF-MT3X65	3	65	3.7	11	0.15	0.19	F15.7	3.5	65	0.038%	C	182	III	1.6X1.2	2.13X1.6	2.82X2.36
XF-MT4X65D	4	65	2.8	11	0.11	0.11	F17.8	2.9	55	0.064%	C	185.6	III	1.2X0.9	1.6X1.2	2.11X1.77
XF-MT4X65	4	65	2.8	11	0.11	0.11	F17.8	2.9	55	0.064%	C	185.6	III	1.2X0.9	1.6X1.2	2.11X1.77
XF-MT6X65	6	65	1.8	11	0.15	0.08	F26.6	2.9	35	0.028%	C	211.8	III	0.8X0.6	1.07X0.8	1.41X1.18
XF-MT6X65D	6	65	1.8	11	0.15	0.08	F26.6	2.9	35	0.028%	C	211.8	III	0.8X0.6	1.07X0.8	1.41X1.18



- 采用物方远心设计，保证测量精准性
- 利用高倍率以及大光圈带来超高分辨率，最高可达210lp/mm
- 全系列工作距离65mm
- 最大可兼容2/3英寸百万像素以上C接口工业相机
- 可应用于高精度工件瑕疵检测